



Effective Date: September 2020

This listing is subject to re-examination in one year.

www.icc-es-pmg.org | (800) 423-6587 | (562) 699-0543

A Subsidiary of the International Code Council®

CSI: DIVISION: 22 00 00—PLUMBING
Section: 22 40 00—Plumbing Fixtures
Section: 22 09 00—Instrumentation and Control for Plumbing

Product certification system:

The ICC-ES product certification system includes testing samples taken from the market or supplier's stock, or a combination of both, to verify compliance with applicable codes and standards. The system also involves factory inspections, and assessment and surveillance of the supplier's quality system

Product: Ceramic Plumbing Fixtures – Water Closets and Urinals

Listee: Advanced Modern Technologies Corp. (AMTC)
8367 Canoga Ave.
Canoga Park, CA 91304
www.amtcorporation.com

Compliance with the following codes:

2021, 2018, 2015, 2012 and 2009 *International Plumbing Code*® (IPC)
2018, 2015, 2012 and 2009 *International Residential Code*® (IRC)
2021, 2018, 2015, 2012 and 2009 *Uniform Plumbing Code*® (UPC)*
2015, 2010 and 2005 *National Plumbing Code of Canada*® (NPC)**
2017 *Uniform Illustrated Plumbing Code – India*™ (UIPC-I)*

**Uniform Plumbing Code* is a copyrighted publication of the International Association of Plumbing and Mechanical Officials

***National Plumbing Code of Canada* is a copyrighted publication of National Research Council Canada

Compliance with the following standards:

ASME A112.19.2 / CSA B45.1-2018 – Ceramic Plumbing Fixtures

Identification:

Each fixture or fixture component must be permanently and legibly marked with the AMTC name or registered trademark and the date of manufacture. Water closets shall be permanently and visibly marked with the model number and gravity flush tanks shall be permanently marked with a water level mark. Water closets and urinals shall be marked with the water consumption in GPF and LPF. Each fixture must bear the ICC-ES PMG listing mark. The ICC-ES PMG listing number (PMG-1228) is optional. All packaging must be marked with the AMTC name or registered trademark; or in case of private labeling, the name of the customer for whom the fixture was manufactured. Packaging for water closets shall be marked with the water consumption in GPF and LPF.

Installation:

Fixtures are to be installed in accordance with the manufacturer's instructions and the applicable code. A water closet or urinal shall not be set closer than 15 inches (381 mm) from its center to any side wall, partition, vanity or other obstruction, or closer than 30 inches (762 mm) center to center

between adjacent fixtures. There shall be not less than a 21-inch (533 mm) clearance in front of the water closet or urinal to any wall, fixture or door. Water closet compartments shall be not less than 30 inches (762 mm) in width and not less than 60 inches (1524 mm) in depth for floor-mounted water closets and not less than 30 inches (762 mm) in width and 56 inches (1422 mm) in depth for wall-hung water closets.

Models:

Pressure Assisted Water Closets

MF1012T11	MF1012AT11	MF1012WT11
MF1012T12	MF1012AT12	MF1012WT12
MF1012T16	MF1012AT16	MF1012WT16
MF1012T16DF	MF1012AT16DF	MF1012WT16DF
AEF1012T11	AEF1012AT11	AEF1012WT11
AEF1012T12	AEF1012AT12	AEF1012WT12
AEF1012T16	AEF1012AT16	AEF1012WT16
AEF1012T16DF	AEF1012AT16DF	AEF1012WT16DF
HSM1012T11	HSM1012AT11	HSM1012WT11
HSM1012T12	HSM1012AT12	HSM1012WT12
HSM1012T16	HSM1012AT16	HSM1012WT16
HSM1012T16DF	HSM1012AT16DF	HSM1012WT16DF
AEFHW1012T11	AEFHW10A12T11	AEFHW1012WT11
AEFHW1012T12	AEFHW1012AT12	AEFHW1012WT12
AEFHW1012T16	AEFHW1012AT16	AEFHW1012WT16
AEFHW1012T16DF	AEFHW1012AT16DF	AEFHW1012WT16DF
AEFC1012T11	AEFC1012AT11	AEFC1012WT11
AEFC1012T12	AEFC1012AT12	AEFC1012WT12
AEFC102T16	AEFC1012AT16	AEFC1012WT16
AEFC1012T16DF	AEFC1012AT16DF	AEFC1012WT16DF
AEFWB1012T11	AEFWB1012AT11	AEFWB1012WT11
AEFWB1012T12	AEFWB1012AT12	AEFWB1012WT12
AEFWB1012T16	AEFWB1012AT16	AEFWB1012WT16
AEFWB1012T16DF	AEFWB1012AT16DF	AEFWB1012WT16DF

Note: Fixture available in White or Biscuit

Pressure Assisted Urinals

MF101812U18	MF101814U18
MF101812U05	MF101814U05
AEF101812U18	AEF101814U18
AEF101812U05	AEF101814U05
HSM101812U18	HSM101814U18
HSM101812U05	HSM101814U05
AEFHW101812U18	AEFHW101814U18
AEFHW101812U05	AEFHW101814U05
AEFC101812U18	AEFC101814U18
AEFC101812U05	AEFC101814U05
AEFWB101812U18	AEFWB101814U18
AEFWB101812U05	AEFWB101814U05

Note: Fixture available in White or Biscuit

Valve Bowls

<u>Model Number</u>	<u>Product Description</u>
AUT-1012	Water Closet Bowl, Rated Flush Volume 1.1 gpf
AUT-1012A	Water Closet Bowl, Rated Flush Volume 1.1 gpf
AUT-1012W	Water Closet Bowl, Rated Flush Volume 1.1 gpf
AUU-1018-12	Urinal Bowl, Rated Flush Volume 0.125 gpf
AUU-1018-14	Urinal Bowl, Rated Flush Volume 0.125 gpf

Note: Fixture available in White or Biscuit

Conditions of Listing:

1. The Advanced Modern Technologies Corp. (AMTC) models recognized in this listing must be installed in accordance with the manufacturer's published installation instructions and the applicable code.
2. The Advanced Modern Technologies Corp. (AMTC) models recognized in this listing are manufactured under a quality control program with annual surveillance inspections by ICC-ES.